



能可靠执行关键打印任务的 Zebra 斑马 140Xi4高性能条码打印机

Zebra 140Xi4条码打印机是 Zebra 系列的经典重工业级条码打印机，它具有坚固、稳定、耐用的特点。Zebra 140Xi4条码打印机是专业为重工业设计的高档工业型，即使是您要求最高的应用程序，您也能信任 Zebra 140Xi4条码打印机为您解难。拥有最大容量为4MB 的 SDRAM，可用快速闪存存贮大量标签格式、图形和字体。能适应日夜连续24小时的运行环境，可承受重工业生产基地灰尘、污染、温度等恶劣的操作环境。Zebra 140xi4条码打印机的高速处理能力和吞吐量、强大的内存、耐用的金属打印头为您带来无限的效率优势。

物理参数

长度 (mm): 393.7 mm
宽度 (mm): 283.2 mm
高度 (mm): 495 mm
重量 (kg): 25 KG
电源电压 (V): 90-265VAC
电源频率 (Hz): 48-62 Hz

性能参数

打印方式: 热敏; 热转印
分辨率 (dpi): 203dpi
打印速度 (mm/s): 356mm/秒
打印宽度: 128mm
打印长度: 991mm 标准内存下
最大纸卷直径: 203mm
纸卷卷心直径: 76mm
标签厚度: 0.076mm 到0.3mm
碳带长度: 300m; 450m
碳带宽度: 51mm-174mm
碳带卷心直径: 25.4mm
碳带外卷最大直径: 81.3mm
处理器&内存: 32位133Mhz RISC 处理器, 8MB 闪存 (包括2MB 用户可用的非易失性内存存储控件, 用于存储可下载内容)
接口类型: RS-232C, IEEE 1284, USB 2.0
字符集: IBM Code Page 850国际字符集
字体: 7种点阵字体, 1种平滑向量字体

使用环境

工作温度 (°C): 0°C-40°C

斑马 ZEBRA 条码打印机 热线电话：400-1199-021 网址：www.jahone.cn

储存温度 (°C)：-40°C-/60°C

工作湿度 (°C)：20-85%无冷凝

存储湿度 (°C)：5-80%无冷凝

支持的软件：ZebraDesigner™ Pro; ZebraDesigner for XML; ZebraNet™ Bridge Enterprise; ZebraNet Utilities v 7.0; Zebra Universal Driver; Additional scalable and bitmapped fonts available

解码能力 (一维)：Code 11, Code 16K, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Csa C Codes, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5, Industrial 2-of-5, interleaved 2 of-5, Logmars, MSI, Codabar, Planet Code

解码能力 (二维)：Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, TLC 39, GS1 DataBar(RSS), Aztec